



TRAY BEARING-MALAYSIA SDN.BHD.



Auto SKF Timken Koyo NSK 6000 6001 6002
 6003 6004 6005 6007 6008 6200 6300 6301 6302
 6303 6304 6305 6306 6308 6314 6410 6411 6412
 6414 Ball Bearings

Bearing No. 6000

6000 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|--------------------------|
| Size | 10x26x8 mm |
| Bore Diameter | 10 mm |
| Outer Diameter | 26 mm |
| Width | 8 mm |
| d | 10 mm |
| D | 26 mm |
| B | 8 mm |
| C | 8 mm |
| r min. | 0,3 mm |
| da min. | 12 mm |
| Da max. | 24 mm |
| ra max. | 0,3 mm |
| Weight | 0,019 Kg |
| Basic dynamic load rating (C) | 4,55 kN |
| Basic static load rating (C0) | 1,95 kN |
| (Grease) Lubrication Speed | 31000 r/min |
| (Oil) Lubrication Speed | 36000 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | KOYO |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.02 |
| Product Group | B00308 |
| | |



TRAY BEARING-MALAYSIA SDN.BHD.

| | |
|---------------------------------|---|
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 10MM Bore; 26MM Outside Diameter; 8MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.koyousa.com |
| Manufacturer Item Number | 6000 |
| Weight / LBS | 0.045 |
| Outside Diameter | 1.024 Inch 26 Millimeter |
| Outer Race Width | 0.315 Inch 8 Millimeter |
| Bore | 0.394 Inch 10 Millimeter |
| Bearing No. | 6000 |
| r(min) | 0.3 |
| Cr | 5.70 |
| C0r | 1.95 |
| Cu | 0.100 |
| f0 | 12.3 |
| | |



TRAY BEARING-MALAYSIA SDN.BHD.

| | |
|------------------|-------|
| Grease lub. | 31000 |
| Oil lub. | 36000 |
| da(min) | 12 |
| Da(max) | 24 |
| ra(max) | 0.3 |
| (Refer.)Mass(kg) | 0.019 |